

Accessories



PS2 is the traditional mechanical pressure switch for pumps control up to 1,5 kW (2HP), single-phase power supply 110÷230 V, protection degree IP20 and female hydraulic connection G1/4".

Ref.	Factory setting	Pressure range
ACP1555	1,5÷2,8 bar	1,5÷5,5 bar
ACP2575	2,8÷4 bar	2,5÷7,5 bar
ACP4010	4÷5,5 bar	4÷10 bar



PS2+ is the traditional mechanical pressure switch for pumps control up to 1,5 kW (2HP), single-phase power supply 110÷230 V, protection degree IP54 and swivel female hydraulic connection G1/4" in order to make easier the assembly.

Ref.	Factory setting	Pressure range
ACP1065	1,4÷2,8 bar	1,0÷6,5 bar



Our traditional mechanical pressure switch type PS2 integrated in a 3-ways fitting with inner non-return valve and pressure gauge.

Ref.	Factory setting	Pressure range
ACT1555	1,5÷2,8 bar	1,5÷5,5 bar
ACT2575	2,8÷4 bar	2,5÷7,5 bar
ACT4010	4÷5,5 bar	4÷10 bar



Stainless steel 5-ways fitting with inner non-return valve. Ideal for systems with hydropneumatic tank, with 2 inlets for pressure gauge and sensor element (transducer, pressure switch, ...).

Ref.	Dimensions
ACT0001	G1"(M) x G1"(F) x G1"(F) x G1/4"(F) x G1/4"(F)
ACT0005	G1,25"(M) x G1,25"(F) x G1"(F) x G1/4"(F) x G1/4"(F)
ACT0006	G1,5"(M) x G1,5"(F) x G1"(F) x G1/4"(F) x G1/4"(F)



4-ways fitting with inner non-return valve and integrated pressure gauge. There is a G1/4" female inlet in brass for the assembly of a pressure switch, a pressure transmitter or any other fitting.

Ref.	Dimensions
ACT0002	G1"(M) x G1"(F) x G1"(F) x G1/4"(F)