

	Modelo	Conexión Hidráulica	Potencia Máx.	Montaje	Presión Puesta en Marcha	Posibilidad de Schuko Integrado
	Controlpump	G1" M > G1" F	2 HP / 1,5 kW ~1x110 / 230 V (10 A)	90°	1,2 bar 1,5 bar 2,2 bar 1,5 - 2,5 bar	NO
	Controlmatic	G1" M > G1" M	2 HP / 1,5 kW ~1x110 / 230 V (10 A)	90°	1,2 bar 1,5 bar 2,2 bar 1,5 - 2,5 bar	Sí
	Compact 1	G1" M > G1" M NPT 1" > NPT 1"	2 HP / 1,5 kW ~1x110 - 230 V (10 A)	180°	1,5 l/min	NO
	Compact 2		2 HP / 1,5 kW ~1x110 - 230 V (10 A)	180°	1,0 bar 1,5 bar 2,5 bar	NO
	Compact 22		3 HP / 2,2 kW ~1x110 - 230 V (16 A)	180°	1,5 - 3,5 bar	NO
	Compact 3		2 HP / 1,5 kW ~1x110 - 230 V (10 A)	180°	1,5 bar 2,5 bar	NO
	Optimatic	G1" M > G1" M NPT 1" > NPT 1"	2 HP / 1,5 kW ~1x110 / 230 V (10 A)	180°	1,5 bar 2,2 bar 1,5 - 3 bar	Sí
	Optimatic 22		3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	1,5 - 3 bar	Sí
	Optimatic DC 24V		0.5 HP / 0,38 kW	180°	1,5 bar	NO
	Optiplus	G1-1/4" M > G1-1/4" M	3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	1,5 - 3 bar	NO
	Digimatic 1	G1" M > G1" M	3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	marcha: 0,5 - 7 bar paro: 1 - 8 bar	NO
	Digimatic 2	G1" M > G1" M		180°		NO
	Digiplus	G1-1/4" M > G1-1/4" M		180°		NO
	Onematic	G1-1/4" M > G1-1/4" M	~3x400 V (10 A) ~3x230 V (10 A) ~1x230 V (10 A)	180°	marcha: 0,5 - 6,5 bar paro: 1 - 7 bar	NO
	EPR	G1" > G1" NPT 1" > NPT 1" G1-1/4" > G1-1/4" NPT 1-1/4" > NPT 1-1/4"	3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	marcha: 1 - 4,5 bar trabajo: 2 - 6 bar	NO
	DPR				marcha: 0,5 - 5,5 bar trabajo: 2 - 6 bar	
	DPR MASTER					
	DPR ALT					