

	Modelo	Conexión Hidráulica	Potencia Máx.	Montaje	Presión Puesta en Marcha	Posibilidad de Schuko Integrado
	Controlpump	G1" M > G1" F	2 HP / 1,5 kW	90°	1,2 bar 1,5 bar 2,2 bar 1,5-2,5 bar	NO
	Controlmatic	G1" M > G1" M	2 HP / 1,5 kW	90°	1,2 bar 1,5 bar 2,2 bar 1,5-2,5 bar	SÍ
	Compact 1	G1" M > G1" M NPT 1" > NPT 1"	2 HP / 1,5 kW ~1x110-230 V (10 A)	180°	1,5 l/min	NO
	Compact 2		2 HP / 1,5 kW ~1x110-230 V (10 A)	180°	1,0 bar 1,5 bar 2,5 bar 1,5-3,5 bar	NO
	Compact 22		3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	1,5-3,5 bar	NO
	Compact 3		2 HP / 1,5 kW ~1x110-230 V (10 A)	180°	1,5 bar 2,5 bar	NO
	Optimatic	G1" M > G1" M	2 HP / 1,5 kW	180°	1,5 bar 2,2 bar 1,5-3 bar	SÍ
	Optimatic 22	G1" M > G1" M	3 HP / 2,2 kW	180°	1,5-3 bar	SÍ
	Optimatic DC 24V	G1" M > G1" M	0.5 HP / 0,38 kW	180°	1,5 bar	NO
	Optiplus	G1-1/4" M > G1-1/4" M	3 HP / 2,2 kW	180°	1,5-3 bar	NO
	Digimatic 1	G1" M > G1" M	3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	0,5-7 bar	NO
	Digimatic 2	G1" M > G1" M		180°	marcha: 0,5-7 bar paro: 1-8 bar	NO
	Digiplus	G1-1/4" M > G1-1/4" M		180°		NO
	Onematic	G1-1/4" M > G1-1/4" M	~3x400 V (10 A) ~3x230 V (10 A) ~1x230 V (10 A)	180°	marcha: 0,5-6,5 bar paro: 1-7 bar	NO
	EPR	G1" > G1" NPT 1" > NPT 1" G1-1/4" > G1-1/4" NPT 1-1/4" > NPT 1-1/4"	3 HP / 2,2 kW ~1x110-230 V (16 A)	180°	marcha: 1 - 5 bar trabajo: 2 - 6 bar	NO
	DPR					
	DPR MASTER					
	DPR ALT					
					marcha: 0,5-5,5 bar trabajo: 2-6 bar	