

	Modelo	Conexión Hidráulica	Potencia Máx.	Montaje	Presión Puesta En Marcha	Posibilidad de Schuko Integrado
	Controlpump	G1" M > G1" F	2 HP (1,5 kW)	90°	1,2 bar 1,5 bar 2,2 bar 1,5-2,5 bar	NO
	Controlmatic	G1" M > G1" M	2 HP (1,5 kW)	90°	1,2 bar 1,5 bar 2,2 bar 1,5-2,5 bar	Sí
	Optimatic	G1" M > G1" M	2 HP (1,5 kW)	180°	1,5 bar 2,2 bar 1,5-3 bar	Sí
	Optimatic 22	G1" M > G1" M	3 HP (2,2 kW)	180°	1,5-3 bar	Sí
	Optimatic DC 12V	G1" M > G1" M	0,25 HP (0,19 kW)	180°	1,5 bar	NO
	Optimatic DC 24V	G1" M > G1" M	0,5 HP (0,38 kW)	180°	1,5 bar	NO
	Optiplus	G1 1/4" M > G1 1/4" M	3 HP (2,2 kW)	180°	1,5-3 bar	NO
	Digimatic 1	G1" M > G1" M	~1x110-230 V (16 A)	180°	R	NO
	Digimatic 2	G1" M > G1" M	~1x110-230 V (16 A)	180°	R	NO
	Digiplus	G1 1/4" M > G1 1/4" M	~1x110-230 V (16 A)	180°	R	NO
	Onematic	G1 1/4" M > G1 1/4" M	~3x400 V (10 A) ~3x230 V (10 A) ~1x230 V (10 A)	180°	R	NO
	Onematic easy	G1 1/4" M > G1 1/4" M	~1x230 V (16 A)	180°	R	NO
	Compact 1	G1" M > G1" M	2 HP (1,5 kW)	180°	1,5 l/min	NO
	Compact 2	G1" M > G1" M	2 HP (1,5 kW)	180°	1,0 bar 1,5 bar 1,5-4,5 bar	NO
	Compact 22	G1" M > G1" M	3 HP (2,2 kW)	180°	1,0 bar 1,5 bar 1,5-4,5 bar	NO
	Compact 3	G1" M > G1" M	2 HP (1,5 kW)	180°	1,5 bar 2,2 bar	NO